

initial set up

<b>Blade</b>	<b>inboard</b>	<b>outboard</b>	<b>P/C link adjustment</b>	
<b>target</b>			1 barrel turn= 6 flats	1/2 turn coarse clevis≈ 10 flats
<b>blank</b>			1/2 turn fine clevis≈7 flats	1 flat≈ 1.5mm

		ground		hover					
		target	blank	target	blank	target	blank	target	blank
	track	separation (in.);		separation (in.);		separation (in.);		separation (in.);	
	balance	LT	VT	LT	VT	LT	VT	LT	VT
		IPS		IPS		IPS		IPS	
		angle		angle		angle		angle	
action taken;									
	track	separation (in.);		separation (in.);		separation (in.);		separation (in.);	
	balance	LT	VT	LT	VT	LT	VT	LT	VT
		IPS		IPS		IPS		IPS	
		angle		angle		angle		angle	
action taken;									
	track	separation (in.);		separation (in.);		separation (in.);		separation (in.);	
	balance	LT	VT	LT	VT	LT	VT	LT	VT
		IPS		IPS		IPS		IPS	
		angle		angle		angle		angle	
action taken;									
	track	separation (in.);		separation (in.);		separation (in.);		separation (in.);	
	balance	LT	VT	LT	VT	LT	VT	LT	VT
		IPS		IPS		IPS		IPS	
		angle		angle		angle		angle	
action taken;									
	track	separation (in.);		separation (in.);		separation (in.);		separation (in.);	
	balance	LT	VT	LT	VT	LT	VT	LT	VT
		IPS		IPS		IPS		IPS	
		angle		angle		angle		angle	
action taken;									
	track	separation (in.);		separation (in.);		separation (in.);		separation (in.);	
	balance	LT	VT	LT	VT	LT	VT	LT	VT
		IPS		IPS		IPS		IPS	
		angle		angle		angle		angle	
action taken;									